### (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

# (19) World Intellectual Property Organization International Bureau



### - 1 CHAN CHINDON A CONTRACTOR CHAN CONTRACTOR AND CONTRACTOR CHAN CONTRACTOR CONTRACTOR CONTRACTOR CONTRACTOR

(43) International Publication Date 1 July 2004 (01.07.2004)

PCT

## (10) International Publication Number WO 2004/054773 A1

(51) International Patent Classification<sup>7</sup>: 39/00, B29D 11/00, 17/00 // B29K 83:00

B29C 39/02,

(21) International Application Number:

PCT/IB2003/005435

(22) International Filing Date:

26 November 2003 (26.11.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

02080272.4 13 December 2002 (13.12.2002)

(71) Applicant (for all designated States except US): KONIN-

Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL];

- (72) Inventors; and
- (75) Inventors/Applicants (for US only): VAN SANTEN, Helmar [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). STAPERT, Hendrik, R. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). KLOOSTERBOER, Johan, G. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (74) Agents: DEGUELLE, Wilhelmus, H., G. et al.; Philips Intellectual Property & Standards, Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK,

MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

#### Declaration under Rule 4.17:

as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

### Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD OF MANUFACTURING A REPLICA, AS WELL AS A REPLICA OBTAINED BY CARRYING OUT A UV LIGHT-INITIATED OR THERMAL CURING TREATMENT OF A REACTIVE MIXTURE

(57) Abstract: The present invention relates to a method of manufacturing a replica, which method comprises the provision of a curable resin composition between a mold and a substrate or a blank, carrying out a UV light-initiated or thermal curing treatment and removing the replica thus manufactured from the mold, which replica comprises the substrate and the reproduction of the mold provided thereon. The invention also relates to a replica obtained by carrying out a UV light-initiated or thermal curing treatment of a reactive compound, especially a replica that has a high transparency for low wavelengths, i.e. 190-400 nm.

